



SLOPE DECK Properly Prepared Substrate/
1/4" TO 1'-0" TO DRAIN 2.01-2.12 General Guidelines

| Step | Products | Coverage | Dry Mills |
|------|--|-----------------------|-----------|
| 1 | Enviro-Grip® EP#1 or EP#2 Primer | 1 gal. / 300 sq.ft. | 3 |
| 2E | E-Tuff®-100 (with Rubber) | 3 gal. / 100 sq.ft. | 42 ± 2 |
| 2P | P-Tuff™ Classic (with Rubber) | 3 gal. / 100 sq.ft. | 42 ± 2 |
| 3 | Sand Broadcast | . | . |
| 4 | Topshield™ EST or ALP-150 or Chem-Sentry™ II or Stalntuff™ | 1 gal. / 100 sq.ft. | 10 ± 2 |
| 5 | Topshield™ EST or ALP-150 or Chem-Sentry™ II or Stalntuff™ (Recommended) | 3/4 gal. / 100 sq.ft. | 8 ± 2 |

- Notes:
1. E-Tuff®-100 Base Material is a mixture of 4 part E-Tuff®-100 and 1 part of water by volume.
 2. P-Tuff™ Base Material is a mixture of 4 part P-Tuff™ Classic, SLV, or Flex and 1 part of water by volume.
 3. Repair Crack and Joints 2.09-2.12 General Guidelines

NOT TO SCALE

Rev. 5-29-17



8550 West Desert Inn Road
Suite 102-451
Las Vegas, NV 89117
P | 1-866-977-8833
F | 1-800-904-0182
www.polytuffus.com
sales@polytuffus.com

DETAIL NAME & DESCRIPTION:

**Flexideck E-tuff and P-tuff
Edge Termination
(Typical)**

DESIGNED

B. CLANTON

SHEET

1 of 1

DRAWN

M. HELMANDOTTAR

SCALE

N.T.S

DATE

5/25/17

DETAIL NO.

WD-1