


Step	Products	Coverage	Dry Mils
1	Metal Lath		
2E	E-Tuff@-100 Sand Slurry (over Metal Lath)	6 gal. / 100 sq.ft.	95 ± 2
2P	P-Tuff™ Sand Slurry (over Metal Lath)	6 gal. / 100 sq.ft.	89 ± 2
3	Topshield™ EST or ALP-150 or Chem-Sentry™ II or Stalntuff™	1 1/4 gal. / 100 sq.ft.	13 ± 2
4	Topshield™ EST or ALP-150 or Chem-Sentry™ II or Stalntuff™	3/4 gal. / 100 sq.ft.	8 ± 2

Notes: 1. E-Tuff@-100 Base Material is a mixture of 4 part E-Tuff@-100 and 1 part of water by volume.
 2. P-Tuff™ Base Material is a mixture of 4 part P-Tuff™ Classic, SLV, or Flex and 1 part of water by volume.
 3. Repair Crack and Joints 2.09-2.12 General Guidelines

NOT TO SCALE 5-26-17

 Poly-Tuff Systems International	8550 West Desert Inn Road Suite 102-451 Las Vegas, NV 89117 P 1-866-977-8833 F 1-800-804-0182 www.polytuffus.com sales@polytuffus.com	DETAIL NAME & DESCRIPTION: Flexideck E-tuff and P-tuff Metal Lath Edge Termination (Typical)	DESIGNED B. CLANTON	SHEET 1 of 1
			DRAWN M. HELMANDOTTAR	SCALE N.T.S
			DATE 5/25/17	DETAIL NO. ML-1