



NOTES:

1. APPLY PRIMER TO CONCRETE AND METAL FLASHINGS AT 300 SQ/FT P/GAL AND ALLOW PRIMER TO DRY
2. APPLY PRIMER AND ALLOW PRIMER TO DRY (PRIMER OPTIONAL ON PLYWOOD)
3. APPLY P-TUFF CLASSIC AT 40 SQ/FT P/GALLON
4. APPLY P-TUFF CLASSIC AT 100 SQ/FT P/GALLON
5. BROADCAST AGGREGATE TO REFUSAL
6. APPLY COMPLETE FLEXIDECK SYSTEM AS SPECIFIED

- \* P-TUFF™ BASE MATERIAL IS A MIXTURE OF 4 PART P-TUFF™ CLASSIC, SLV OR FLEX AND 1 PART OF WATER BY VOLUME
- \* THE ICC-ES # AND FIRE RATING
- \* REPAIR CRACKS AND JOINTS 2.09-2.12 GENERAL GUIDELINES



Poly-Tuff Systems International

8550 West Desert In Road  
Suite 102-451  
Las Vegas, NV 89117  
P 1-866-977-8833  
F 1-800-804-0182  
www.polytuffus.com  
sales@polytuffus.com

DETAIL NAME & DESCRIPTION

**FLEXIDECK™ P-TW**  
**ICC-ES #ESR-2785**  
**Tile-Underlayment**  
**Waterproofing System-Plywood**

DESIGNED <b>B. CLANTON</b>	SHEET <b>1 OF 1</b>
DRAWN <b>N. BASTANI</b>	SCALE <b>N.T.S</b>
DATE <b>5/18/2017</b>	DETAIL NO. <b>P-TW</b>