



INSTA-THICK™

A Thickener for Horizontal Membranes and Sealants

1.01 DESCRIPTION

Insta-Thick™ is a recycled material that is treated and made waterproof before being refined and ground to an ultra-fine dry powder to be used as thickener for horizontal membranes and sealants to create a higher viscosity material. The range thickening may be field controlled to create a slope grade, roller grade, vertical grade and even overhead grade material. The product was specially formulated for PolyTuff Systems to be utilized within the epoxy, urethane coatings and sealants without significantly changing the physical properties of the cured product. Insta-Thick™ allows for the adjustment of fluid membranes and sealants to accommodate changes in weather and climate conditions. The material is “field adjusted” by the desired amount of Insta-Thick™ incorporated into the liquid membrane for sealant. Please use the correct product grade that complies with VOC regulations as per federal, state, county and city regulations/codes at the place of installation of product.

1.02 FEATURES

- Consistent Surface Finish
- Easily Dispersed
- Easy Mixing
- Field Adjusted
- Labor Saving
- Lightweight
- Saves Inventories
- Ultra-Violet Stable
- User Friendly

1.03 TYPICAL USES

- Basements
- Field or Shop Adjusted
- Foundation Coatings
- Green Roof Waterproofing Epoxies
- Isolation Membranes
- Liquid Applied Waterproofing Roofing Materials
- Roof Repair
- Roofing Joints

1.04 COLOR

Medium grey

1.05 PACKAGING

5 gallon (18.9 liters) pail

1.06 MIXING

Open Insta-Thick™ 5 gallon (18.9 liters) pail and slowly mix and break apart any lumps. Add to the liquid membrane or sealant and mix slowly until the Insta-Thick™ is completely wet out and thoroughly mixed into the coating or sealant. If the coating or sealant becomes too thick, add more of the horizontal material until it reaches the desired viscosity. Mix any lumpy materials until a smooth consistency is achieved.

APPLICATION

2.01 APPLICATION BASICS

Always apply material on a disposable item to test the viscosity. Create a horizontal “sag line” to measure any slump or sag characteristics. Mockups of materials with Insta-Thick™ are recommended to evaluate the volume necessary to achieve the desired thickness. Record the approximate weight of volume of material used to create the desired thickness and duplicate as needed to complete the project.

2.02 STORAGE

Insta-Thick™ has a shelf life of six (6) months from date of manufacture in original, factory-sealed containers when stored indoors at a temperature between 60-95°F (15-35°C).

2.03 LIMITATIONS

- Insta-Thick™ is intended for materials to be used in the same day as the product is mixed into the membrane, epoxy, paint or sealant.
- Insta-Thick™ should be stored in a sealed, water-tight container and not left unsealed where humidity may excessively clump the powder. Hand mixing is not recommended.

Please read all information in the General & Safety Guidelines, Technical Data Sheets, Guide Specifications and Safety Data Sheets (SDS) before applying material. PSI Products are for "Professional Use Only" and preferably applied by professionals who have prior experience with PSI Products or have undergone training in application of PSI Products. Published technical data and instructions are subject to change without notice. Contact your local PSI representative or visit our website for current technical data, instructions, and project specific recommendations.

LIMITED WARRANTY

PSI warrants its products to be free of manufacturing defects and that they will meet PSI current published physical and chemical properties. Seller's sole responsibility shall be to replace that portion of the product which proves to be defective. There are no other warranties by PSI of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. PSI shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. PSI shall not be responsible for use of this product in a manner to infringe on any patent held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded from the limited warranty. PSI reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator.

DISCLAIMER

All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and test, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his use of the product. We do not suggest or guarantee that any hazard listed herein are the only ones which may exist. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements, whether in writing or oral, other than those contained herein shall not be binding upon the manufacturer, unless in writing and signed by a corporate officer of the manufacturer. Technical and application information is provided for the purpose of establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and PSI makes no claim that these tests or any other tests, accurately represent all environments.