

Features of P-Tuff® Flexideck® Systems

FACTS ABOUT P-TUFF® FLEXIDECK® SYSTEMS

- Water-catalyzed Elastomeric
- · Environmentally Friendly
- User Friendly
- Non Gassing For Applying in Any Thickness
- · Highly Resilient
- Fast Curing with the Ability to Control Cure Times
- Tough Weather Resistant Waterproof System
- Improved Slip-resistant Surface Available in Various Textures and Finishes

- Class-A Fire Rated System On Plywood and Concrete
- · Economical, Minimal Waste
- One Day Installation
- · Easy to Repair
- Labor Cost Efficient
- · Joint and Crack Free
- Can Be Applied at Low Temperature Up to 20°F (-6.6°C)

TYPICAL USAGE

GENERAL REPAIRING	RESIDENTIAL & COMMERCIAL	INDUSTRIAL & OTHERS
 Caulking Sealant Patching Concrete Repair Crack Filling Expansion Joint Seismic Joint Sloping Concrete Freeze Thaw Protection Deck Substrates Easy Installation Fast Cure Repair 	 Vehicular Parking Decks Balconies, Patios & Plazas Pedestrian Walk Surfaces Athletic & Game Surfaces Fitness Centers & Exercise Floors Play Surfaces Kitchen Floor Ski Industry Surfaces & Coverings Tile Underlayment & Shower Pans Pool Decks 	 Dairy Surfaces Equestrian Surfaces Mechanical Rooms Ship & Boat Decks Animal Habitat Floors Food Processing Areas Tank & Pond Liners Shock Absorptive Surfaces Computer Chip Manufacturing Plants Static Spark Resistance Manufacturing Plants Concrete Repair

© POLY-TUFF SYSTEMS INTERNATIONAL CORPORATION MARCH 2017