

## **POLY-TUFF SYSTEMS INTERNATIONAL**

2250 E. Tropicana Ave  
Suite 19-600  
Las Vegas, NV 89119



Phone: (866) 977-8833  
Fax: (800) 804-0182  
Email: [sales@polytuffus.com](mailto:sales@polytuffus.com)  
Web: [www.polytuffus.com](http://www.polytuffus.com)

# **PSI Tech-Note**

September 2007

## **Cooling Tower Waterproof Coating System Enviro-Grip #1 Primer, E-Tuff 100 and B-Tuff 5600**

It is acceptable to utilize Enviro-Grip #1 primer, E-Tuff 100, water catalyzed polyurea with Thixo (vertical applications) and E-Tuff 100 without Thixo for cooling tower base coat applications. A top coat of B-Tuff 5600 not less than 20 dft must be applied over the E-Tuff 100 in both vertical and horizontal applications. Approximately of four hours cure time for the E-Tuff 100 will be necessary or until the E-Tuff 100 is completely dry to touch before the B-Tuff 56000 may be applied as the top coat.

Each application should be in strict accordance with the related PSI data sheet and good waterproofing practice. Please call 866.977.8833 if there are any questions regarding the Flexideck Systems.

***Bob Clanton***

National Sales Manager  
702.343.7067